iranphp
articles

عنوان مقاله :   تابع ساخت ورودی تاریخ
نگارنده :   ....
آدرس پست الکترونیک :   ....
تاریخ نگارش :   ....

تابع ساخت ورودی تاریخ:

```php
<?php
   //  Make Date Box function
   //  Written by Mohammad Dehghanpour
   //  Email: m_dehghanpour@hotmail.com

   function MakeDateBox($method,$name="")
   {

      $CurrentYear = Date(Y);
      $monthArray = array("", "January", "February", "March", "April", "May", "June", "July",
"August", "September", "October", "November", "December");

      $yContainer= "y".$name; // make var for year.
      $mContainer= "m".$name; // make var for month.
      $dContainer= "d".$name; // make var for day.


    // Put previous value of user submit in these dynamic vars.
       $$yContainer= $method[$yContainer];
     $$mContainer= $method[$mContainer];
     $$dContainer= $method[$dContainer];


     // make the day field
       echo "<select name=". $dContainer .">";
     echo "<option value=''>Day</option>";
     for ($i=1; $i<=31; $i++)
     {
         $str = "<option value=" . sprintf("%02d", $i);

        // check for previous value of user submit.
          if ($i == $$dContainer)
            $str .= " selected";

        $str .= ">" . sprintf("%02d", $i) . "</option>";
         echo $str;
     }
     echo "</select>";


     // make the month field
     echo "<select name=m". $name .">";
     echo "<option value=''>Month</option>";
       for ($i=1; $i<=12; $i++)
     {
         $str = "<option value=" . sprintf("%02d", $i);

        // check for previous value of user submit.
        if ($i == $$mContainer)
             $str .= " selected";

         $str .= ">" . $monthArray[$i] . "</option>";
        echo $str;
     }
     echo "</select>";
```

```php
    // make the year field
    echo "<select name=y" . $name . ">";
    echo "<option value=''>Year</option>";
    for ($i=$CurrentYear; $i>=($CurrentYear-2); $i--)
    {
        $str = "<option value=$i";

        // check for previous value of user submit.
        if ($i == $$yContainer)
            $str .= " selected";

        $str .= ">" . sprintf("%04d", $i) . "</option>";
        echo $str;
    }
    echo "</select>";

  }// End function.
?>


    <!---------------------- An example ---------------------->
<div align='center'>
<form action="<?=$_SERVER[PHP_SELF]?>" method="POST">
<?
    // you can left the first argument empty if you wanna make only one date group, like this:
MakeDateBox($_POST);
    // and then you will get tree vaiable named [y, m, d] from post or get.
    echo "From:";
    MakeDateBox($_POST,"From");
    echo"      To:";
    MakeDateBox($_POST,"To");
?>
   <input type="Submit" style='border:1px solid #eeeee5;color:000000;' value="   Hit ">
</form>
</div>
<?
    if(!empty($_POST))
    {
        // get maked variables.
        echo "From:".$_POST[yFrom]."-".$_POST[mFrom]."-".$_POST[dFrom];
        echo "</br>";
        echo "To:".$_POST[yTo]."-".$_POST[mTo]."-".$_POST[dTo];
    }
?>
```