

maryam_mpf@yahoo.com:

)

-
- ' - Filteration
 - ' - Drain
 - ' - Geotextile
 - ' - Geosynthetic

(

[]

[]

:[]

.[] ()

()
[] ()

.[]

EOS: اندازه مؤثر روزنها می باشد یعنی اندازهای که ۹۰ درصد روزنها ریزتر از آنند.

- Polyethylene
- Polyester
- polypropylene
- Polyamide (nylon)

)

(

.[]

)

. (

.[]

[]

(k_g)

[] (k_s)

-

USAG

GR

KO

LTC

(

) HCR

Koerner

Abouzakhm ,Williams

[]

()

()

[]

Valcros

$\frac{gr}{m^2}$
(Giroud,)
Leclercq

New Esna

$\frac{gr}{m^2}$

[]

$\frac{gr}{m^2}$

New Esna

Yangtze

San xia

(-)

[]

()

[]

[]

[]

[]

- [1] Corbett, S. P., "The Design and Specification of Geotextiles and Geocomposites for Filtration and Drainage", International Conference on Geotextiles in Filtration and Drainage, Cambridge, sep. 23th, 1992.
 - [2] Ingold, T. s., "Geotextiles in Filtration and Drainage", International Conference on Geotextiles in Filtration and Drainage, Cambridge, sep. 23th, 1992.
 - [3] Jones, C. J. F. P., "Geosynthetic Reinforced Soil in Retaining Walls", Geosynthetic-Reinforced Soil Retaining Walls , P: 103-108.
 - [4] Koerner, R. M., "Emerging and Future Developments of Selected Geosynthetic Applications", Journal of Geotechnical and Geo environmental Engineering, April 2000, P: 293-306.
 - [5] Pinto, M. I. M. (), "Application of Geosynthetics for Soil Reinforcement", Ground Improvement, NO. , pp. - .